

DTM InkJet Label Stock

# DTM Paper Matte Nature (MN)

## Description

DTM Paper Matte Nature label materials have been designed specifically for applications where an recycled, authentic, natural and ecological look is desired. It has excellent inkjet print quality with low saturation settings and fast ink drying time, ideal for applications printing variable information in conjunction with full-colour graphics.

## Face Stock

Uncoated white paper, made of 100% recycled fibres. Due to its recycled nature recycled particles can be observed. Suitable for high-resolution and high-speed dye based and pigmented ink jet printing.

## Adhesive

General purpose acrylic adhesive, waterborne.

## Liner

White kraft, woodfree.

## Packaging and Shelf Life

Continuous or die-cut label rolls with identification labels. Each label roll is individually packed with a plastic bag. Keep label rolls in their plastic bags, in room temperature, away from direct sunlight and/or heat sources. Under ideal storage conditions, shelf life is four years.

## Product Usage

All DTM Genuine certified InkJet-materials are the ideal choice for labels printed on any colour label printer. Proper testing in the final application environment is recommended especially when used near water or chemicals. As with all pressure-sensitive materials, this product should be tested thoroughly with the chosen label printer under end-user conditions to ensure it will meet the requirements of the specific application.

## Technical Specifications

### Face

Weight:	70	g/m <sup>2</sup>	ISO 536
---------	----	------------------	---------

Thickness:	87	µm	ISO 534
------------	----	----	---------

### Adhesive

Loop Tack:	8	N	FTM9
------------	---	---	------

### Liner/Backing

Weight:	51	g/m <sup>2</sup>	ISO 536
---------	----	------------------	---------

Thickness:	54	µm	ISO 534
------------	----	----	---------

### Performance

Total caliper:	158 µm
----------------	--------

### Minimum Application

Temperature:	5°C
--------------	-----

Service Temperature:	-20°C to 100°C
----------------------	----------------



**Ihr Drucker-Partner:  
Karley Deutschland GmbH**

Herner Str. 15b, 45657 Recklinghausen  
Tel: 02361-979231-55, Fax: 02361-979231-90, Email: info@karley.eu